According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MasterSeal 440 limestone

Product code : 00000000050127576

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub: Product for construction chemicals

stance/Mixture

Recommended restrictions

on use

: Industrial use, Professional use, Consumer use

1.3 Details of the supplier of the safety data sheet

Company : Master Builders Solutions

Yapı Kimyasalları Sanayi ve Ticaret Ltd.

Sti.,

Ataşehir Kuzey, C Kapısı 3E/ 5-12

34746 İstanbul, Turkey

Telephone : +902162178800

Telefax : +902162178800

E-mail address of person responsible for the SDS

mabas-eb@mbcc-group.com

1.4 Emergency telephone

ChemTel: +1-813-248-0585

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Respiratory sensitization, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

2.2 Label elements

Labeling T.R. SEA No 28848

Hazard pictograms



According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

Signal Word : Danger

Hazard Statements : H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Precautionary Statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P284 In case of inadequate ventilation wear respiratory pro-

tection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

Disposal:

P501 Dispose of contents/container to appropriate hazard-

ous waste collection point.

Additional Labeling:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : polyurethane

Fillers pigments

Components

Chemical name	CAS-No. EC-No. Index-No. Registration num- ber	Classification	Concentration (% w/w)
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8 202-966-0 615-005-00-9	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT SE3; H335 STOT RE2; H373	< 1
xylene	1330-20-7 215-535-7	Flam. Liq.3; H226 Acute Tox.4; H332	>= 1 - <= 5

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

	601-022-00-9	Acute Tox.4; H312 Skin Irrit.2; H315	
trimethoxy(3- (oxiranylmethoxy)propyl)silane	2530-83-8	Eye Dam.1; H318	< 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Call a physician or poison control center immediately.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Dry powder

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid dust formation.
Avoid breathing dust.

Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Date of last issue: -Version Revision Date: SDS Number:

000000452791 Date of first issue: 31.12.2020 31.12.2020 1.0

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

Advice on protection against

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

When using do not eat or drink. When using do not smoke. Hygiene measures

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must

comply with the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, well-ventilated

place. Protect from direct sunlight. Store protected against

freezing.

Advice on common storage Observe TRGS 509/510 storage rules.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice Specific use(s)

mentioned in this section 7 is to be observed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
xylene	1330-20-7	TWA (8 Hour)	50 ppm	TR OEL		
-		, ,	221 mg/m3			
	Further inform	Further information: A skin notation assigned to the OEL identifies the possi-				
	bility of significant uptake through the skin.					
		STEL 15 min	100 ppm	TR OEL		
			442 mg/m3			
		TWA	50 ppm	2000/39/EC		

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

	221 mg/m3		
Further information: Identifies the possibility of significant uptake through the skin, Indicative			
STEL	100 ppm 442 mg/m3	2000/39/EC	
STEL value	100 ppm 442 mg/m3	OEL (TR)	
TWA value	50 ppm 221 mg/m3	OEL (TR)	

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Hand protection

Remarks : Suitable chemical resistant safety gloves (EN 374) also with

prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

Skin and body protection : Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Protective measures : Avoid contact with the skin, eyes and clothing.

No special measures necessary if stored and handled correct-

ly.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste
Color : pale beige
Odor : characteristic
pH : Not applicable

Melting point : Not applicable

boiling temperature : Not applicable

Flash point : > 65 °C

Evaporation rate : The product is a non-volatile solid.

Flammability (solid, gas) : not flammable

Vapor pressure : not determined

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

Relative vapor density : The product is a non-volatile solid.

Density : 1,20 - 1,25 g/cm3

Solubility(ies)

Water solubility : insoluble (23 °C)

Partition coefficient: n-

octanol/water

: not applicable for mixtures

Autoignition temperature : Not applicable

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Not explosive

Oxidizing properties : not fire-propagating

9.2 Other information

Self-heating substances : No data available

Metal corrosion rate : Corrosive effects to metal are not anticipated.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : See SDS section 7 - Handling and storage.

10.5 Incompatible materials

Materials to avoid : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

10.6 Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Diphenylmethane-4,4'-diisocyanate (MDI):

Partition coefficient: n- : log Pow: 4,51 (22 °C)

octanol/water pH: 7

Method: Partition coefficient (n-octanol/water), HPLC method.

GLP: no

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2 Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour. H312 : Harmful in contact with skin. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Resp. Sens. : Respiratory sensitization

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

OEL (TR) : Regulation on Protection of Health & Safety Measures from

Risks related to Chemical Agents at Work (Turkey)

TR OEL : Turkey. Chemical Agents at Work - Annex I: Indicative occu-

pational exposure limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

OEL (TR) / STEL value : Short Term Exposure Limit (STEL): OEL (TR) / TWA value : Time Weighted Average (TWA):

TR OEL / TWA (8 Hour) : Measured or calculated in relation to a reference period of

eight-hour time-weighted average

TR OEL / STEL 15 min : A limit value above which exposure should not occur and is

related to a 15-minute priod, unless otherwise specified

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MasterSeal 440 limestone

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000452791 Date of first issue: 31.12.2020

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SDS Author

Name: Nazlı ÖZER

Address: Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti. 34746 Ataşehir -

Istanbul, Turkey

Phone: +90 262 751-6845

Email: nazli.ozer@mbcc-group.com Certificate no: KDU-A-0-0077 Certification Date: 29.07.2020 Certificate Expiry Date: 29.07.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN