

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MasterSeal NP 474 aluminium grey
Product code : 000000000050498420

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Product for construction chemicals

1.3 Details of the supplier of the safety data sheet

Company : Master Builders Solutions
Yapı Kimyasalları Sanayi ve Ticaret Ltd.
Sti.,
Ataşehir Kuzey, C Kapısı 3E/ 5-12
34746 İstanbul, Turkey

Telephone : +902162178800

Telefax : +902162178800

E-mail address of person responsible for the SDS : product-safety@mbcc-group.com

1.4 Emergency telephone

ChemTel: +1-813-248-0585

National Emergency Telephone Number : Acil İlkyardım Merkezi: 112 Ulusal Zehir Danışma Merkezi: 114
İtfaiye: 110

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848 and subsequent amendments

Respiratory sensitization, Category 1 : H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2 Label elements

Labeling T.R. SEA No 28848 and subsequent amendments

Hazard pictograms :



SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version 1.0 Revision Date: 06.04.2022 SDS Number: 000000793252 Date of last issue: -
Date of first issue: 06.04.2022

Signal Word : Danger

Hazard Statements : H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary Statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P284 In case of inadequate ventilation wear respiratory protection.

Response:
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Disposal:
P501 Dispose of contents/container to appropriate hazardous waste collection point.

Additional Labeling:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Preparation based on:
isocyanate
additives

Components

Chemical name	CAS-No. EC-No. Index-No. KKDIK Registration No.	SEA Classification	Concentration (% w/w)
xylene	1330-20-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 1 - <= 5
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8 202-966-0 615-005-00-9	Acute Tox. 4; H332 Skin Irrit. 2; H315	< 1

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version 1.0 Revision Date: 06.04.2022 SDS Number: 000000793252 Date of last issue: -
Date of first issue: 06.04.2022

		Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory system) specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % STOT SE 3; H335 >= 5 %	
trimethoxy(3-(oxiranylmethoxy)propyl)silane	2530-83-8 219-784-2	Eye Dam. 1; H318 Aquatic Chronic 3; H412	< 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do NOT induce vomiting.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

6.2 Environmental precautions

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Pick up with inert absorbent material (e.g. sand, earth etc.).
Dispose of contaminated material as prescribed.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Product is not explosive.

Normal measures for preventive fire protection.

Hygiene measures : When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version 1.0 Revision Date: 06.04.2022 SDS Number: 000000793252 Date of last issue: -
Date of first issue: 06.04.2022

Advice on common storage : Observe TRGS 509/510 storage rules.
Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA (8 Hour)	50 ppm 221 mg/m ³	TR OEL
		Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.		
		STEL 15 min	100 ppm 442 mg/m ³	TR OEL
		Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.		
		TWA	50 ppm 221 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Hand protection

Remarks : Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

- Respiratory protection : Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type ABEK).
- Protective measures : Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : pasty
- Color : various
- Odor : characteristic
- pH : not determined
- Melting temperature : not determined
- boiling temperature : not determined
- Flash point : does not flash
- Vapor pressure : No data available
- Density : 1,17 - 1,23 g/cm³ (20 °C)
- Solubility(ies)
Water solubility : No data available
- Autoignition temperature : not determined
- Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.
- Explosive properties : Not explosive
- Oxidizing properties : not determined

9.2 Other information

- Self-ignition : not self-igniting

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	00000793252	Date of first issue: 06.04.2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : See SDS section 7 - Handling and storage.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

10.6 Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

mation

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

KKDIK (30105 (Bis)) - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex 17) : Conditions of restriction for the following entries should be considered: Number on list 3

Diphenylmethane-4,4'-diisocyanate (MDI) (Number on list 56)

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	00000793252	Date of first issue: 06.04.2022

Regulation on Persistent Organic Pollutants (Number 30595 and subsequent amendments published) : Not applicable

Regulation on prevention of major industrial accidents. Reg number 30702 : Not applicable

Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

T.R. Regulation on Classification, Labeling and Packaging of Substances and Mixtures, dated December 11, 2013 and numbered 28848 from the Ministry of Environment and Urbanization and the subsequent amendments published.

Regulation on health and safety measures regarding working with chemicals (Number: 28733, 2013). Occupational Exposure Limit Values (Annex 1)

15.2 Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapor.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitization
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

- | | | |
|-----------------------|---|--|
| 2000/39/EC | : | Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| TR OEL | : | Turkey. Chemical Agents at Work - Annex I: Indicative occupational exposure limit values |
| 2000/39/EC / TWA | : | Limit Value - eight hours |
| 2000/39/EC / STEL | : | Short term exposure limit |
| TR OEL / TWA (8 Hour) | : | Measured or calculated in relation to a reference period of eight-hour time-weighted average |
| TR OEL / STEL 15 min | : | A limit value above which exposure should not occur and is related to a 15-minute period, unless otherwise specified |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SDS Author

Name: Nazlı ÖZER
Address: Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti. 34746 Ataşehir - Istanbul, Turkey
Phone: +90 262 751-6845
Email: nazli.ozer@mbcc-group.com
Certificate no: KDU-A-0-0077
Certification Date: 29.07.2020
Certificate Expiry Date: 29.07.2025

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



MasterSeal NP 474 aluminium grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2022	000000793252	Date of first issue: 06.04.2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN