According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

000000792008 Date of first issue: 31.12.2020 31.12.2020 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MSeal NP 474 Black TR 0,6L 5H4

Product code : 00000000050497231

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-

: Product for construction chemicals stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company Master Builders Solutions

Yapı Kimyasalları Sanayi ve Ticaret Ltd.

Ataşehir Kuzey, C Kapısı 3E/5-12

34746 İstanbul, Turkey

Telephone : +902162178800

Telefax : +902162178800

E-mail address of person responsible for the SDS

mabas-eb@mbcc-group.com

1.4 Emergency telephone

Acil İlk Yardım Merkezi: 112 Ulusal Zehir Danışma Merkezi: 114 İtfaiye: 110

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Respiratory sensitization, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

2.2 Label elements

Labeling T.R. SEA No 28848

Hazard pictograms

Signal Word Danger

Hazard Statements May cause allergy or asthma symptoms or breathing H334

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version **Revision Date:** SDS Number: Date of last issue: -

31.12.2020 000000792008 Date of first issue: 31.12.2020 1.0

difficulties if inhaled.

Precautionary Statements Prevention:

> Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P284 In case of inadequate ventilation wear respiratory pro-

tection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

Disposal:

P501 Dispose of contents/container to appropriate hazard-

ous waste collection point.

Additional Labeling:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature isocyanate

additives

Components

Chemical name	CAS-No. EC-No. Index-No. Registration num- ber	Classification	Concentration (% w/w)
xylene	1330-20-7	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315	>= 1 - <= 5
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8 202-966-0 615-005-00-9	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT SE3; H335 STOT RE2; H373	< 1
trimethoxy(3- (oxiranylmethoxy)propyl)silane	2530-83-8 219-784-2	Eye Dam.1; H318 Aquatic Chronic3;	< 1

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

H412

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- :

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact.

No special measures necessary provided product is used

correctly.

Advice on protection against : Product is not explosive.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using, do not eat, drink or smoke. Hands and/or face

should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

 Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Advice on common storage : Observe TRGS 509/510 storage rules.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the relevant identified use(s) listed in Section 1 the advice

mentioned in this section 7 is to be observed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
xylene	1330-20-7	TWA (8 Hour)	50 ppm	TR OEL	
			221 mg/m3		
	Further information: A skin notation assigned to the OEL identifies the possi-				
	bility of significant uptake through the skin.				
		STEL 15 min	100 ppm	TR OEL	
			442 mg/m3		
		TWA	50 ppm	2000/39/EC	
			221 mg/m3		
	Further information: Identifies the possibility of significant uptake through the				
	skin, Indicative				
		STEL	100 ppm	2000/39/EC	
			442 mg/m3		
		STEL value	100 ppm	OEL (TR)	
			442 mg/m3		

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

TWA value 50 ppm OEL (TR) 221 mg/m3

8.2 Exposure controls

Personal protective equipment

Eye protection

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Hand protection

Remarks : Suitable chemical resistant safety gloves (EN 374) also with

prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

Skin and body protection : Body protection must be chosen depending on activity and

possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or

EN ISO 13982 in case of dust).

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type

ABEK).

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : pasty
Color : various
Odor : characteristic
pH : not determined

Melting temperature : not determined

boiling temperature : not determined

Flash point : does not flash

Flammability (solid, gas) : not flammable

Vapor pressure : No data available

Density : 1,17 - 1,23 g/cm3 (20 °C)

Solubility(ies)

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

Water solubility : No data available Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : not determined

9.2 Other information

Self-ignition : not self-igniting

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : See SDS section 7 - Handling and storage.

10.5 Incompatible materials

Materials to avoid : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

10.6 Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Diphenylmethane-4,4'-diisocyanate (MDI):

Partition coefficient: n- : log Pow: 4,51 (22 °C)

octanol/water pH: 7

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version **Revision Date:** SDS Number: Date of last issue: -

000000792008 Date of first issue: 31.12.2020 31.12.2020 1.0

Method: Partition coefficient (n-octanol/water), HPLC method.

GLP: no

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

Product:

Additional ecological infor- : No data available

mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2 Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour. H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Hazardous to the aquatic environment - chronic hazard

Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids Resp. Sens. : Respiratory sensitization

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

OEL (TR) : Regulation on Protection of Health & Safety Measures from

Risks related to Chemical Agents at Work (Turkey)

TR OEL : Turkey. Chemical Agents at Work - Annex I: Indicative occu-

pational exposure limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

OEL (TR) / STEL value : Short Term Exposure Limit (STEL): OEL (TR) / TWA value : Time Weighted Average (TWA):

TR OEL / TWA (8 Hour) : Measured or calculated in relation to a reference period of

eight-hour time-weighted average

TR OEL / STEL 15 min : A limit value above which exposure should not occur and is

related to a 15-minute priod, unless otherwise specified

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

SDS Author

Name: Nazlı ÖZER

Address: Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti. 34746 Ataşehir -

Istanbul, Turkey

Phone: +90 262 751-6845

Email: nazli.ozer@mbcc-group.com
Certificate no: KDU-A-0-0077
Certification Date: 29.07.2020
Certificate Expiry Date: 29.07.2025

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



MSeal NP 474 Black TR 0,6L 5H4

Version Revision Date: SDS Number: Date of last issue: -

1.0 31.12.2020 000000792008 Date of first issue: 31.12.2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN