

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey
Product code : 000000000056497670

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Product for construction chemicals

1.3 Details of the supplier of the safety data sheet

Company : Sika MBCC Turkey Yapı Kimyasalları Sanayi ve Ticaret Limited Şirketi
Ataşehir Kuzey, C Kapısı 3E/ 5-12
34746 İstanbul, Turkey
Telephone : +902162178800
Telefax : +902162178800
E-mail address of person responsible for the SDS : product-safety@mbcc-group.com

1.4 Emergency telephone

ChemTel: +1-813-248-0585
National Emergency Telephone Number : Acil İlk Yardım Merkezi: 112 Ulusal Zehir Danışma Merkezi: 114 İtfaiye: 110

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848 and subsequent amendments

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labeling T.R. SEA No 28848 and subsequent amendments

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.

Precautionary Statements : P102 Keep out of reach of children.

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P261 Avoid breathing dust.

P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P315 Get immediate medical advice/ attention.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Hazardous ingredients which must be listed on the label:

Cement, portland, chemicals

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version 1.0 Revision Date: 16.12.2022 SDS Number: 000000274288 Date of last issue: -
Date of first issue: 16.12.2022

Chemical nature : modified cement mortar

Components

Chemical name	CAS-No. EC-No. Index-No. KKDIK Registration No.	SEA Classification	Concentration (% w/w)
Cement, portland, chemicals	65997-15-1 266-043-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)	>= 30 - < 50
Substances with a workplace exposure limit :			
Titanium dioxide	13463-67-7 236-675-5 022-006-00-2		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with acid.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Containers should be stored tightly sealed in a dry place.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version 1.0 Revision Date: 16.12.2022 SDS Number: 000000274288 Date of last issue: -
Date of first issue: 16.12.2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Cement, portland, chemicals	65997-15-1	ZOAD/TWA	80 mg/m ³ / %SiO ₂ +2	TR OEL DU
	Further information: Allowable occupational exposure limit values of mineral dusts			
		ZOAD/TWA (Total dust)	15 mg/m ³	TR OEL DU
	Further information: Allowable occupational exposure limit values of chemicals in dust form			
		ZOAD/TWA (Respirable dust)	5 mg/m ³	TR OEL DU
	Further information: Allowable occupational exposure limit values of chemicals in dust form			
Titanium dioxide	13463-67-7	ZOAD/TWA (Total dust)	15 mg/m ³	TR OEL DU
	Further information: Allowable occupational exposure limit values of chemicals in dust form			

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Breathing protection if dusts are formed.

Filter type : Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2) (Particle filter EN 143 P2 or FFP2)

Protective measures : Avoid contact with the skin, eyes and clothing.
Avoid inhalation of dusts.
In order to prevent contamination while handling, closed working clothes and working gloves should be used.
Handle in accordance with good building materials hygiene

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	powder
Color	:	white to grey
Odor	:	odorless
Odor Threshold	:	Not determined due to potential health hazard by inhalation.
pH	:	12 - 13 (20 °C)
Melting point	:	> 2.000 °C
Boiling point	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	The product is a non-volatile solid.
Flammability (solid, gas)	:	not flammable
Upper explosion limit / Upper flammability limit	:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Lower explosion limit / Lower flammability limit	:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Vapor pressure	:	No data available
Relative vapor density	:	The product is a non-volatile solid.
Bulk density	:	1.800 - 2.400 kg/m ³ (20 °C)
Solubility(ies) Water solubility	:	dispersible (20 °C)
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

Viscosity
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : not fire-propagating

9.2 Other information

Self-heating substances : No data available

Metal corrosion rate : No corrosive effect on metal.

Self-ignition : not self-igniting

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : See SDS section 7 - Handling and storage.

10.5 Incompatible materials

Materials to avoid : Strong bases
Strong acids

10.6 Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version 1.0	Revision Date: 16.12.2022	SDS Number: 000000274288	Date of last issue: - Date of first issue: 16.12.2022
----------------	------------------------------	-----------------------------	--

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory tract irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Not applicable for inorganic substances.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to its consistency and insolubility in water.

12.4 Mobility in soil

Product:

Distribution among environmental compartments : Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.
The substance will not evaporate into the atmosphere from the water surface.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

KKDIK (30105 (Bis)) - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex 17) : Not applicable

Regulation on Persistent Organic Pollutants (Number 30595 and subsequent amendments published) : Not applicable

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

Regulation on prevention of major industrial accidents. Reg number 30702

Not applicable

Other regulations:

T.R. Regulation on Classification, Labeling and Packaging of Substances and Mixtures, dated December 11, 2013 and numbered 28848 from the Ministry of Environment and Urbanization and the subsequent amendments published.

Regulation on Dust Control (No: 28812, 2013). Occupational Dust Exposure Limit Values (Annex 1)

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2 Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. : Serious eye damage
Skin Irrit. : Skin irritation
STOT SE : Specific target organ toxicity - single exposure
TR OEL DU : Turkey. Regulation on Dust Control. Occupational Dust Exposure Limit Values (Annex 1)
TR OEL DU / ZOAD/TWA : Time Weighted Average Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SikaCeram-565 Pool grey Formerly MasterTile JF 565 grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	16.12.2022	000000274288	Date of first issue: 16.12.2022

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

SDS Author

Name: Nazlı ÖZER

Address: Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti. 34746 Ataşehir - Istanbul, Turkey

Phone: +90 262 751-6845

Email: nazli.ozer@mbcc-group.com

Certificate no: KDU-A-0-0077

Certification Date: 29.07.2020

Certificate Expiry Date: 29.07.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN