According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Product code : 00000000050371721

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended restrictions

on use

: Industrial use, Professional use, Consumer use

1.3 Details of the supplier of the safety data sheet

Company : Sika MBCC Turkey Yapı Kimyasalları

Sanayi ve Ticaret Limited Şirketi Ataşehir Kuzey, C Kapısı 3E/ 5-12

34746 İstanbul, Turkey

Telephone : +902162178800

Telefax : +902162178800

E-mail address of person responsible for the SDS

mabas-eb@mbcc-group.com

1.4 Emergency telephone

ChemTel: +1-813-248-0585

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Skin corrosion/irritation, Category 2 H315: Causes skin irritation.

Serious eye damage/eye irritation, Cate-

gory 1

H318: Causes serious eye damage.

Specific target organ toxicity - single ex-

posure, Category 3

H335: May cause respiratory irritation.

2.2 Label elements

Labeling T.R. SEA No 28848

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

Precautionary Statements : P102 Keep out of reach of children.

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/face protection.

P261 Avoid breathing dust.

P264 Wash face, hands and any exposed skin thoroughly

after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P315 Get immediate medical advice/ attention.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Disposal:

P501 Dispose of contents/container to appropriate hazard-

ous waste collection point.

Hazardous ingredients which must be listed on the label:

Cement, portland, chemicals

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : modified cement mortar

Components

Chemical name	CAS-No. EC-No. Index-No. Registration num-	Classification	Concentration (% w/w)
	ber	01: 1: 2: 0 11045	_
Calcium dihydroxide	1305-62-0 215-137-3	Skin Irrit. 2; H315 Eye Dam. 1; H318	< 5
Coment portland shamingle	65997-15-1	Skin Irrit. 2; H315	< 50
Cement, portland, chemicals		· · · · · · · · · · · · · · · · · · ·	< 50
	266-043-4	Eye Dam. 1; H318	
		STOT SE 3; H335	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

 Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety

standards.

Further information on stor-

age conditions

Containers should be stored tightly sealed in a dry place.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the relevant identified use(s) listed in Section 1 the advice

mentioned in this section 7 is to be observed.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Calcium dihydrox- ide	1305-62-0	TWA (8 Hour)	5 mg/m3	TR OEL	
		TWA (Respirable	1 mg/m3	2017/164/EU	
		fraction)			
	Further information: Indicative				
		STEL (Respira-	4 mg/m3	2017/164/EU	
		ble fraction)	_		
	Further information: Indicative				
		TWA value	5 mg/m3	OEL (TR)	
Quartz (SiO2)	14808-60-7	TWA (Respirable	0,1 mg/m3	2004/37/EC	
. ,		dust)	_		
	Further information: Carcinogens or mutagens				

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Respiratory protection : Breathing protection if dusts are formed.

Filter type : Particle filter with medium efficiency for solid and liquid parti-

cles (e.g. EN 143 or 149, Type P2 or FFP2) (Particle filter EN

143 P2 or FFP2)

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed work-

ing clothes and working gloves should be used.

Handle in accordance with good building materials hygiene

and safety practice.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : powder

Color : gray

Odor : odorless

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : 11 - 12 (20 °C)

Concentration: 100 g/l

Melting point : Not applicable

Boiling point : Not applicable

Flash point : does not flash

Evaporation rate : The product is a non-volatile solid.

Upper explosion limit / Upper

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Lower explosion limit / Lower

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Vapor pressure : No data available

Relative vapor density : The product is a non-volatile solid.

Bulk density : 1.800 - 2.400 kg/m3 (20 °C)

Solubility(ies)

Water solubility : partly miscible (20 °C)

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : Not applicable

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Not explosive

Oxidizing properties : not fire-propagating

9.2 Other information

Self-heating substances : No data available

Metal corrosion rate : No corrosive effect on metal.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : See SDS section 7 - Handling and storage.

10.5 Incompatible materials

Materials to avoid : Strong bases

Strong acids

10.6 Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Chromate in this product has been reduced. Sensitization due

to chromate within stated shelf-live is unlikely.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Not applicable for inorganic substances.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to

its consistency and insolubility in water.

12.4 Mobility in soil

Product:

Distribution among environ-

mental compartments

Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater

is not expected.

The substance will not evaporate into the atmosphere from

the water surface.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

The ingredients of this product are reported in the following inventories:

DSL :

TSCA :

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Full text of other abbreviations

Eve Dam. : Serious eve damage

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

OEL (TR) : Regulation on Protection of Health & Safety Measures from

Risks related to Chemical Agents at Work (Turkey)

TR OEL : Turkey. Chemical Agents at Work - Annex I: Indicative occu-

pational exposure limit values

2004/37/EC / TWA : Long term exposure limit 2017/164/EU / STEL : Short Term Exposure Limit 2017/164/EU / TWA : Limit Value - eight hours

OEL (TR) / TWA value : Time Weighted Average (TWA):

TR OEL / TWA (8 Hour) : Measured or calculated in relation to a reference period of

eight-hour time-weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



SikaTop-582 Seal grey Formerly MasterSeal 582 grey

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.04.2021 000000274428 Date of first issue: 07.04.2021

Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bio-accumulative

Further information

Other information : In addition to the information given in the safety data sheet we

refer to the product specific 'Technical Information'.

SDS Author

Name: Nazlı ÖZER

Address: Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti. 34746 Ataşehir -

Istanbul, Turkey

Phone: +90 262 751-6845

Email: nazli.ozer@mbcc-group.com Certificate no: KDU-A-0-0077 Certification Date: 29.07.2020 Certificate Expiry Date: 29.07.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN