According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604

Version Revision Date: SDS Number: Date of last issue: -

Date of first issue: 28.04.2021 28.04.2021 000000508887 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Product code 000000000050214722

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended restrictions

on use

: Industrial use, Professional use, Consumer use

1.3 Details of the supplier of the safety data sheet

Company Sika MBCC Turkey Yapı Kimyasalları

> Sanayi ve Ticaret Limited Şirketi Ataşehir Kuzey, C Kapısı 3E/5-12

34746 İstanbul, Turkey

Telephone +902162178800

Telefax +902162178800

E-mail address of person responsible for the SDS

mabas-eb@mbcc-group.com

1.4 Emergency telephone

ChemTel: +1-813-248-0585

National Emergency

Acil İlkyardım Merkezi: 112 Ulusal Zehir Danışma Merkezi: 114

Telephone Number İtfaiye: 110

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Acute toxicity, Category 4 H302: Harmful if swallowed.

H332: Harmful if inhaled. Acute toxicity, Category 4

H314: Causes severe skin burns and eye damage. Skin corrosion/irritation, Category 1B

Serious eye damage/eye irritation, Cate-

gory 1

H318: Causes serious eye damage.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

Hazardous to the aquatic environment -

chronic hazard, Category 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labeling T.R. SEA No 28848

Hazard pictograms







Signal Word : Danger

Hazard Statements : H332 Harmful if inhaled.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or

repeated exposure.

H314 Causes severe skin burns and eye damage.H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dusts or mists.

P261 Avoid breathing mist.

P273 Avoid release to the environment.

P272 Contaminated work clothing should not be allowed out

of the workplace.

P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly

after handling.

Response:

P310 Immediately call a POISON CENTER/ doctor/ .?.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting.

P301 + P312 IF SWALLOWED: Call a POISON CENTER/

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

doctor/ .?/ if you feel unwell.

Rinse mouth.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazard-

ous waste collection point.

Hazardous ingredients which must be listed on the label:

Benzyl alcohol

2-piperazin-1-ylethylamine

Formaldehyde, polymer with benzeneamine, hydrogenated

2.3 Other hazards

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Preparation based on:

amine

Components

Chemical name	CAS-No. EC-No. Index-No. Registration num- ber	Classification	Concentration (% w/w)
2-piperazin-1-ylethylamine	140-31-8 205-411-0 612-105-00-4	Acute Tox. 4; H312 Acute Tox. 4; H302 Skin Corr. 1B; H314 Aquatic Chronic 3; H412 Skin Sens. 1; H317	>= 7 - < 10
4,4'-methylenebis(cyclohexylamine)	1761-71-3	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318	>= 3 - < 5

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

		Skin Sens. 1B; H317 STOT RE 2; H373 (Liver, Skeletal muscle) Aquatic Chronic 2; H411	
Formaldehyde, polymer with benzenamine, hydrogenated	135108-88-2	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT RE 2; H373 Aquatic Chronic 3; H412	>= 25 - < 75
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2 202-013-9 603-069-00-0	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 7 - < 10
Benzyl alcohol	100-51-6 202-859-9 603-057-00-5	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 25 - < 50
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0 649-356-00-4	Asp. Tox. 1; H304 Flam. Liq. 1; H224 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	>= 7 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air.

If symptoms persist, seek medical advice.

In case of skin contact : Immediately wash thoroughly with plenty of water, apply ster-

ile dressings, consult a skin specialist.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

In case of eye contact : Immediately wash affected eyes for at least 15 minutes under

running water with eyelids held open, consult an eye special-

ist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wear eye/face protection.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

6.2 Environmental precautions

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up with suitable appliance and dispose of.

Large spills should be collected mechanically (remove by

pumping) for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material.

Keep away from open flames, hot surfaces and sources of

ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: no smoking Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Advice on common storage : Observe

Observe TRGS 509/510 storage rules.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the relevant identified use(s) listed in Section 1 the advice

mentioned in this section 7 is to be observed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Tightly fitting safety goggles (cage goggles) (e.g. EN 166) and

face shield.

Hand protection

Remarks : Suitable chemical resistant safety gloves (EN 374) also with

prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

Skin and body protection : Body protection must be chosen based on level of activity and

exposure.

acid- resp. lye-proof apron, e.g. of rubber (f.e. according to EN

14605)

protection boots, f.e. of rubber (e.g. according to EN 20346) acid-proof chemical protection suit (f.e. according to EN

14605)

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type

ABEK).

Protective measures : Do not inhale dust/fumes/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Color : brownish

Odor : amine-like

Odor Threshold : not determined

pH : 9 - 9,9 (23 °C)

alkaline

Melting point : No data available

Boiling point : No data available

Flash point : 83 °C

Method: Flashpoint test using closed cup, determination of

flashpoint.

Evaporation rate : not determined

Flammability (solid, gas) : not determined

Lower explosion limit / Lower

flammability limit

dropped

Vapor pressure : No data available

Relative vapor density : not determined

Density : 1,01 g/cm3 (23 °C)

Bulk density : Not applicable

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

Solubility(ies)

Water solubility : slightly soluble (23 °C)

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : 750 mPa.s (23 °C)

Explosive properties : Not explosive

Oxidizing properties : not fire-propagating

9.2 Other information

Metal corrosion rate : No corrosive effect on metal.

Self-ignition : not self-igniting

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

10.6 Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

2-piperazin-1-ylethylamine:

Toxicity to fish : LC50 :> 100 mg/l

(trout, rainbow): Exposure time: 96 h

Method: Fish, Acute Toxicity Test: Screening (style of OECD

203) GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 : 32 mg/l

(Daphnia magna): Exposure time: 48 h

Method: Daphnia sp., Acute Immobilisation Test.

GLP: yes

Toxicity to algae/aquatic

plants

EC0: 31 mg/l

(green algae): Exposure time: 72 h Method: Algae, Growth Inhibition Test

GLP: yes

Toxicity to microorganisms : (bacterium):

Exposure time: 17 h Method: other GLP: ves

GLP: yes

(bacterium): Exposure time: 17 h Method: other GLP: yes

EC10: 100 mg/l

EC50 : > 1.000 mg/l

EC10: 100 mg/l

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

EC50 : > 1.000 mg/l

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several

ingredients, the product is estimated not to be readily biode-

gradable according to OECD classification.

Components:

2-piperazin-1-ylethylamine:

Biodegradability : Inoculum: activated sludge, domestic

Concentration: 2 mg/l

Result: Under test conditions no biodegradation observed.

Biodegradation: approx. 0 %

Exposure time: 28 d Method: Closed bottle test

GLP: no data

Inoculum: activated sludge, domestic

Concentration: 28,7 mg/l

Result: Under test conditions no biodegradation observed.

Biodegradation: approx. 18 %

Related to: Dissolved Organic Carbon

Method: Inherent Biodegradability: Modified SCAS Test.

GLP: no data

12.3 Bioaccumulative potential

Components:

Solvent naphtha (petroleum), light arom.:

Partition coefficient: n- : log Pow: 3,17

octanol/water Method: other (calculated)

GLP: no

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : Remarks: The product does not contain a substance fulfilling

the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB

(very persistent/very bioaccumulative) criteria.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Observe national and local legal requirements.

The waste code in accordance with the European waste catalog (EWC) must be specified in cooperation with disposal

agency/manufacturer/authorities.

Residues should be disposed of in the same manner as the

substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

Packs that cannot be cleaned should be disposed of in the

same manner as the contents.

SECTION 14: Transport information

14.1 UN number

ADN : UN 2735
ADR : UN 2735
RID : UN 2735
IMDG : UN 2735
IATA : UN 2735

14.2 UN proper shipping name

ADN : AMINES, LIQUID, CORROSIVE, N.O.S.

(2-PIPERAZIN-1-YLETHYLAMINE, 4,4-METHYLENEBIS(CYCLOHEXYLAMINE))

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.

(2-PIPERAZIN-1-YLETHYLAMINE, 4,4-METHYLENEBIS(CYCLOHEXYLAMINE))

RID : AMINES, LIQUID, CORROSIVE, N.O.S.

(2-PIPERAZIN-1-YLETHYLAMINE, 4,4-METHYLENEBIS(CYCLOHEXYLAMINE))

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.

(2-PIPERAZIN-1-YLETHYLAMINE, 4,4-METHYLENEBIS(CYCLOHEXYLAMINE))

IATA : AMINES, LIQUID, CORROSIVE, N.O.S.

(2-PIPERAZIN-1-YLETHYLAMINE, 4,4-METHYLENEBIS(CYCLOHEXYLAMINE))

14.3 Transport hazard class(es)

ADN : 8
ADR : 8
RID : 8
IMDG : 8
IATA : 8

14.4 Packing group

ADN

Packing group : II Labels : 8

ADR

Packing group : II
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

RID

Packing group : II Hazard Identification Number : 80 Labels : 8

IMDG

Packing group : II Labels : 8

EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo : 855

aircraft)

Packing group : II

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen: 851

ger aircraft)

Packing group : II

Labels : Corrosive

14.5 Environmental hazards

ADN

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

SECTION 16: Other information

Full text of H-Statements

H319

H224 : Extremely flammable liquid and vapor.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

Causes serious eye irritation.

exposure.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

Aquatic Chronic : Hazardous to the aquatic environment - chronic hazard

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SDS Author

Name: Nazlı ÖZER

Address: Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti. 34746 Ataşehir -

Istanbul, Turkey

Phone: +90 262 751-6845

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



Sikafloor P 604 PTB Formerly MasterTop P 604 PTB

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.04.2021 000000508887 Date of first issue: 28.04.2021

Email: nazli.ozer@mbcc-group.com Certificate no: KDU-A-0-0077 Certification Date: 29.07.2020 Certificate Expiry Date: 29.07.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN